## NSN 5962-01-360-5469

Linear Microcircuit - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/5962-01-560-5469
Body Length:
Between 0.195 inches and 0.220 inches
Body Outside Diameter:
Between 0.480 inches and 0.520 inches
Maximum Power Dissipation Rating:
1.5 watts
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and hybrid and thin film and electrostatic sensitive
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
1 input
Design Function And Quantity:
1 amplifier, radio frequency
Current Rating Per Characteristic:
120.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
Hybrid rf amplifier, thin film
Voltage Rating And Type Per Characteristic:
17.0 volts power source
Precious Material And Location:
Header surfaces gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.)
Terminal Type And Quantity:
4 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

## NSN 5962-01-360-5469

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0