NSN 5962-01-361-1587

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-361-1587

View Offline at https://defobasegroup.com/nsn/0302-01-301-1307
Body Length:
Between 0.540 inches and 0.560 inches
Body Width:
Between 0.442 inches and 0.458 inches
Body Height:
Between 0.060 inches and 0.120 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Programmed and ultraviolet erasable and w/enable
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
17 input
Case Outline Source And Designator:
C-12 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.3 volts input and 6.5 volts input
Capitance Rating Per Characteristic:
12.00 input picofarads and 14.00 output picofarads
Time Rating Per Chacteristic:
300.00 nanoseconds access
Memory Device Type:
Eprom
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
32 leadless
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5962-01-361-1587

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0