NSN 5962-01-361-2747

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-361-2747

view Online at https://aerobasegroup.com/nsn/5962-01-361-2747
Body Length:
Between 0.165 inches and 0.185 inches
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Maximum Power Dissipation Rating:
658.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and high speed
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 comparator
Case Outline Source And Designator:
A-1 mil-m-38510
Current Rating Per Characteristic:
18.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-16.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
30.00 nanoseconds delay
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0