NSN 5962-01-361-2765

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-361-2765

View Online at https://aerobasegroup.com/nsn/5962-01-361-2765
Body Length:
0.540 inches
Body Width:
Between 0.340 inches and 0.396 inches
Body Height:
Between 0.045 inches and 0.092 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and static operation
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
18 input
Criticality Code Justification:
Feat
Current Rating Per Characteristic:
120.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Capitance Rating Per Characteristic:
6.00 input picofarads and 7.00 output picofarads
Time Rating Per Chacteristic:
45.00 nanoseconds access
Memory Device Type:
Ram
Special Features:
Nuclear hardness critical item
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:

20 flat leads

NSN 5962-01-361-2765

Memory Microcircuit - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0