NSN 5962-01-361-4982

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-361-4982

| Body Length: |
|---|
| Between 1.559 inches and 1.591 inches |
| Body Width: |
| Between 1.559 inches and 1.591 inches |
| Body Height: |
| Between 0.145 inches and 0.155 inches |
| Operating Tempurature Range: |
| -35.0/+85.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Hac/rmpe react basic |
| Features Provided: |
| Electrostatic sensitive |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Pin grid array |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Criticality Code Justification: |
| Cbbl |
| Design Function And Quantity: |
| 1 processor, input/output |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| Microcircuit, asic, communications processor |
| Voltage Rating And Type Per Characteristic: |
| 4.5 volts input and 5.5 volts input |
| Hybrid Technology Type: |
| Monolithic |
| Nuclear Hardness Critical Feature: |
| Hardened |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.) |
| Terminal Type And Quantity: |
| 181 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5962-01-361-4982

Hybrid Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0