NSN 5962-01-361-6482

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-361-6482

Body Length:
0.960 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.130 inches and 0.185 inches
Operating Tempurature Range:
-55.0/+115.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and positive outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
13 input
Criticality Code Justification:
Feat
Design Function And Quantity:
1 amplifier, sense
Case Outline Source And Designator:
D-6 mil-m-38510
Current Rating Per Characteristic:
50.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-7.0 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
65.00 nanoseconds delay
Special Features:
Nuclear hardness critical item
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
18 printed circuit
Shelf Life:
N/a
Unit Of Measure:

NSN 5962-01-361-6482

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0