NSN 5962-01-361-6484

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-361-6484 **Body Length:** 1.280 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 0.5 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and 3-state output and w/clock and w/disable and w/enable and bidirectional **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Design Function And Quantity:** 1 transceiver and 1 receiver **Case Outline Source And Designator:** D-9 mil-m-38510 **Current Rating Per Characteristic:** 100.00 milliamperes forward current, peak total value not applicable **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source **Capitance Rating Per Characteristic:** 10.00 input pascal industrial light tank stock and 12.00 output pascal industrial light tank stock **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5962-01-361-6484

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0