# NSN 5962-01-361-6515

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-361-6515

## **Body Length:**

Between 0.442 inches and 0.460 inches

## **Body Width:**

Between 0.442 inches and 0.460 inches

## **Body Height:**

Between 0.060 inches and 0.100 inches

# Maximum Power Dissipation Rating:

1.2 watts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and burn in and monolithic and programmed and electrostatic sensitive

#### Inclosure Material:

Ceramic

## Inclosure Configuration:

Leadless flat pack

## **Output Logic Form:**

Transistor-transistor logic

## Input Circuit Pattern:

22 input

#### **Case Outline Source And Designator:**

C-4 mil-m-38510

## **Current Rating Per Characteristic:**

180.00 milliamperes reverse current, dc absolute

## **Terminal Surface Treatment:**

Solder

### **Product Name:**

Registered and-or logic array

## Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

#### **Time Rating Per Chacteristic:**

30.00 nanoseconds delay

#### Memory Device Type:

Pal

## Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

# Terminal Type And Quantity:

28 leadless

### Shelf Life:

N/a

# NSN 5962-01-361-6515

Memory Microcircuit - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

