NSN 5962-01-362-1124

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-362-1124

view Offilite at https://defobasegroup.com/nsi//0302-01-302-1124
Body Length:
1.060 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.130 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and positive outputs and monolithic and bidirectional
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Design Function And Quantity:
8 transceiver
Case Outline Source And Designator:
D-8 mil-m-38510
Current Rating Per Characteristic:
5.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Capitance Rating Per Characteristic:
10.00 input picofarads and 12.00 output picofarads
Time Rating Per Chacteristic:
12.00 nanoseconds delay
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 printed circuit
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5962-01-362-1124

Digital Microcircuit - Page 2 of 2



em			

No

Fiig:

A458a0