

View Online at <https://aerobasegroup.com/nsn/5962-01-362-3533>

Body Length:

0.840 inches

Body Width:

0.310 inches

Body Height:

0.200 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

High speed and retriggerable and w/reset

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

Dual 3 input

Design Function And Quantity:

2 multivibrator, monostable

Case Outline Source And Designator:

D-2 mil-m-38510

Current Rating Per Characteristic:

-25.00 milliamperes average forward current averaged over a full 60-hz cycle and 25.00 milliamperes average forward current averaged over a full 60-hz cycle

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts negative power supply span and 7.0 volts positive power supply span

Test Data Document:

96909-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0