

View Online at <https://aerobasegroup.com/nsn/5962-01-362-3533>

**Body Length:**

0.840 inches

**Body Width:**

0.310 inches

**Body Height:**

0.200 inches

**Maximum Power Dissipation Rating:**

500.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

High speed and retriggerable and w/reset

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

Dual 3 input

**Design Function And Quantity:**

2 multivibrator, monostable

**Case Outline Source And Designator:**

D-2 mil-m-38510

**Current Rating Per Characteristic:**

-25.00 milliamperes average forward current averaged over a full 60-hz cycle and 25.00 milliamperes average forward current averaged over a full 60-hz cycle

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-0.5 volts negative power supply span and 7.0 volts positive power supply span

**Test Data Document:**

96909-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0