## NSN 5962-01-362-7380

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-362-7380

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
330.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Milstar
Features Provided:
Electrostatic sensitive and hermetically sealed and monolithic and radiation hardened and negative outputs and positive outputs
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
2 input
Criticality Code Justification:
Feat
Design Function And Quantity:
1 comparator, voltage
Case Outline Source And Designator:
A-1 mil-m-38510
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, linear, voltage comparator
Voltage Rating And Type Per Characteristic:
30.0 volts power source
Special Features:
Electrostatic discharge sens/hardness critical item; military p/n m38510/10304bga, cage 81349; nha p/n 6499-332450, cage 80070
Nuclear Hardness Critical Feature:
Hardened
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 pin

N/a

Shelf Life:

## NSN 5962-01-362-7380

Linear Microcircuit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0