

View Online at <https://aerobasegroup.com/nsn/5962-01-363-0915>

**Operating Temperature Range:**

-55.0/+100.0 degrees celsius 1st memory-55.0/+125.0 degrees celsius 2nd memory

**Component Function Relationship:**

Unmatched

**Features Provided:**

Programmed

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Metal oxide-semiconductor logic 1st memorybipolar metal-oxide semiconductor 2nd memory

**Design Function And Quantity:**

2 prom program table

**Case Outline Source And Designator:**

D-3 mil-m-38510 1st memoryd-8 mil-m-38510 2nd memory

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit devices, eprom/prom

**Microcircuit Device Type And Quantity:**

2 memory

**Voltage Rating And Type Per Characteristic:**

-0.3 volts absolute input and 7.0 volts absolute input

**Time Rating Per Characteristic:**

450.00 nanoseconds access 1st memory70.00 nanoseconds access 2nd memory

**Memory Device Type:**

Eeprom err-100 err-100rom err-100 err-100

**Terminal Type And Quantity:**

24 case 1st memory20 case 2nd memory

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0