## NSN 5962-01-363-2449



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-363-2449 **Body Length:** 1.062 inches **Body Width:** 0.250 inches **Maximum Power Dissipation Rating:** 490.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 1430-01-087-6330 **Features Provided:** Bipolar and schottky **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Design Function And Quantity:** 1 arithmetic logic unit **Case Outline Source And Designator:** D-8 mil-m-38510 **Current Rating Per Characteristic:** 65.00 milliamperes supply **Terminal Surface Treatment:** Solder **Product Name:** Bicmos arithmetic logic units **Voltage Rating And Type Per Characteristic:** -0.5 volts absolute input and 7.0 volts absolute input **Test Data Document:** 81349-mil-m-38510a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 20 printed circuit Shelf Life: N/a **Unit Of Measure:** 

Yes - demil/mli

**Demilitarization:** 

## NSN 5962-01-363-2449

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0