

View Online at <https://aerobasegroup.com/nsn/5962-01-363-3440>

Maximum Power Dissipation Rating:

1.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

An/gpn-22&tpn e/i fscm 49956

Features Provided:

Programmed

Inclosure Material:

Ceramic

Inclosure Configuration:

Flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Case Outline Source And Designator:

F-6 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital fused prom

Voltage Rating And Type Per Characteristic:

-0.5 volts absolute input and 7.0 volts absolute input

Time Rating Per Characteristic:

25.00 nanoseconds af output megawatts

Memory Device Type:

Prom

Test Data Document:

49956-g504229 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

24 printed circuit

Specification Data:

67268-5962-88735/tx/ government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0