## NSN 5962-01-363-4973

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-363-4973

Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
An/gpn-22&tpn e/i fscm 49956
Features Provided:
Programmed
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Bipolar metal-oxide semiconductor
Case Outline Source And Designator:
D-9 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts absolute input and 7.0 volts absolute input
Memory Device Type:
Pal
Test Data Document:
49956-g504228 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
24 printed circuit
Specification Data:
67268-5962-86053/tx/ government standard
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:
A458a0
Demilitarization: Yes - demil/mli Fiig: