

View Online at <https://aerobasegroup.com/nsn/5962-01-364-1268>

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

6605-01-313-1810

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Design Function And Quantity:

1 gate, array

Case Outline Source And Designator:

D-5 mil-m-38510

Product Name:

Microcircuit, digita (gate array) readout

Voltage Rating And Type Per Characteristic:

-0.5 volts absolute input and 15.0 volts absolute input

Special Features:

Microcircuits shall be glassivated

Precious Material And Location:

Package cavity gold

Precious Material:

Gold

Special Test Features:

Gold eutectic die bond used in package cavity

Test Data Document:

94580-10082097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

40 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0