# NSN 5962-01-364-1999

Memory Microcircuit - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5962-01-364-1999

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+15.0 degrees celsius

## End Application:

Display conso e/i fscm 49956

## **Features Provided:**

Programmed

#### **Inclosure Material:**

Ceramic

## Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Bipolar metal-oxide semiconductor

**Case Outline Source And Designator:** 

#### D-2 mil-m-38510

## **Terminal Surface Treatment:**

Solder

## **Product Name:**

Bipolar prom

#### Voltage Rating And Type Per Characteristic:

5.5 volts absolute input and 7.0 volts absolute input

## Memory Device Type:

Prom

## **Test Data Document:**

49956-979735-107 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### Terminal Type And Quantity:

16 printed circuit

#### **Specification Data:**

96906-mil-std-883/tx/ government standard

## Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

## Fiig:

A458a0