## NSN 5962-01-364-7981

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-364-7981

| Operating Tempurature Range:   |
|--|
| +0.0/+70.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Burn in and electrostatic sensitive  |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Output Logic Form:   |
| Transistor-transistor logic  |
| Input Circuit Pattern:   |
| 25 input   |
| Design Function And Quantity:  |
| 1 microprocessor   |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| 20.0 volts power source  |
|  |
| Terminal Type And Quantity:  |
| Terminal Type And Quantity: 40 printed circuit   |
|  |
| 40 printed circuit   |
| 40 printed circuit Shelf Life:   |
| 40 printed circuit  Shelf Life: N/a  |
| 40 printed circuit  Shelf Life: N/a Unit Of Measure:   |
| 40 printed circuit  Shelf Life: N/a Unit Of Measure:   |
| 40 printed circuit  Shelf Life: N/a Unit Of Measure: Demilitarization:                       |
| 40 printed circuit  Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli       |
| 40 printed circuit  Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: |
| 40 printed circuit  Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: |