

View Online at <https://aerobasegroup.com/nsn/5962-01-364-9372>

**Maximum Power Dissipation Rating:**

2.0 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Scadc e/i fscm k0656

**Features Provided:**

Programmed

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Bipolar metal-oxide semiconductor

**Input Circuit Pattern:**

16 input

**Case Outline Source And Designator:**

D-8 mil-m-38510

**Current Rating Per Characteristic:**

100.00 milliamperes reverse current, dc

**Terminal Surface Treatment:**

Solder

**Product Name:**

16-input 6-output registered and-or gate array

**Voltage Rating And Type Per Characteristic:**

-0.5 volts absolute input and 12.0 volts absolute input

**Memory Device Type:**

Pal

**Hybrid Technology Type:**

Monolithic

**Terminal Type And Quantity:**

20 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0