

View Online at <https://aerobasegroup.com/nsn/5962-01-365-2262>

**Maximum Power Dissipation Rating:**

550.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Burn in and electrostatic sensitive and monolithic and programmed and ultraviolet erasable

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Leadless flat pack

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

14 input

**Case Outline Source And Designator:**

C-12 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-2.0 volts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

90.00 nanoseconds propagation delay

**Memory Device Type:**

Eprom

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

32 leadless

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0