## NSN 5962-01-365-2435

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-365-2435

Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Burn in and electrostatic sensitive
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 driver, nand
Terminal Surface Treatment:
Solder
Solder Voltage Rating And Type Per Characteristic:
Voltage Rating And Type Per Characteristic:
Voltage Rating And Type Per Characteristic: 7.0 volts power source
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity:
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 14 printed circuit
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life:
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure:
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure:
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization:
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli
Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: