## NSN 5962-01-365-5096

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-365-5096

Body Length:
2.045 inches
Body Width:
1.145 inches
Body Height:
0.160 inches
Maximum Power Dissipation Rating:
2.86 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Countermeasur e/i fscm 97942
Features Provided:
Hybrid
Inclosure Material:
Glass or ceramic
Inclosure Configuration:
Flat pack
Design Function And Quantity:
1 attenuator, variable
Terminal Surface Treatment:
Gold
Product Name:
Microcircuit, hybrid, digital attenuator
Voltage Rating And Type Per Characteristic:
-0.5 volts applied and 7.0 volts applied
Hybrid Technology Type:
Multichip
Special Features:
Critical chip=defined as that chip which will be the most highly thermally stressed for any case temperature, t/c.
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
76 printed circuit
Specification Data:

81349-mil-m-38510 government specification and 96906-mil-std-1772 government standard and mil-g-45204 government standard

## NSN 5962-01-365-5096

Hybrid Microcircuit - Page 2 of 2



16170-7520150

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0