

View Online at <https://aerobasegroup.com/nsn/5962-01-365-6028>

**Maximum Power Dissipation Rating:**

192.5 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Imulator e/i fscm 76301

**Features Provided:**

Bipolar

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Bipolar metal-oxide semiconductor

**Input Circuit Pattern:**

6 input

**Design Function And Quantity:**

6 driver

**Case Outline Source And Designator:**

D-1 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Product Name:**

Hex driver

**Voltage Rating And Type Per Characteristic:**

-0.5 volts applied and 7.0 volts applied

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

14 printed circuit

**Specification Data:**

67268-5962-88731 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0