## NSN 5962-01-365-6037

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-365-6037

_	_	_			_
o	odv		٦n	~+	h.
0	uuv	ᄔ	31 I	uι	II.

Between 1.430 inches and 1.485 inches

**Body Width:** 

Between 0.245 inches and 0.310 inches

**Body Height:** 

Between 0.155 inches and 0.200 inches

**Operating Tempurature Range:** 

+0.0/+70.0 degrees celsius

**Storage Tempurature Range:** 

-65.0/+150.0 degrees celsius

**Features Provided:** 

High speed and low power and ultraviolet erasable and w/disable

**Inclosure Material:** 

Ceramic

**Inclosure Configuration:** 

Dual-in-line

**Output Logic Form:** 

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:** 

18 input

**Current Rating Per Characteristic:** 

100.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:** 

Solder

**Product Name:** 

Power switched and reprogrammable

**Voltage Rating And Type Per Characteristic:** 

-0.5 volts power source and 7.0 volts power source

**Capitance Rating Per Characteristic:** 

10.00 input picofarads and 10.00 output picofarads

Time Rating Per Chacteristic:

65.00 nanoseconds access

**Memory Device Type:** 

Prom

**Terminal Type And Quantity:** 

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

**Demilitarization:** 

Yes - demil/mli

## NSN 5962-01-365-6037

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0