

View Online at <https://aerobasegroup.com/nsn/5962-01-366-1057>

Body Length:

0.840 inches

Body Width:

0.310 inches

Body Height:

0.185 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and monolithic and positive outputs and 3-state output

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

6 input

Case Outline Source And Designator:

D-2 mil-m-38510

Current Rating Per Characteristic:

85.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Capitance Rating Per Characteristic:

5.00 input picofarads and 8.00 output picofarads

Time Rating Per Chacteristic:

65.00 nanoseconds delay

Memory Device Type:

Prom

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0