## NSN 5962-01-366-1458

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-366-1458 **Body Length:** 0.405 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 1.2 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Wideband and fast settling and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 amplifier, operational, general purpose **Case Outline Source And Designator:** D-4 mil-m-38510 **Current Rating Per Characteristic:** 23.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Product Name:** Current feedback operational amplifier **Voltage Rating And Type Per Characteristic:** -7.0 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 15.00 nanoseconds settling **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 

N/a

**Unit Of Measure:** 

8 printed circuit Shelf Life:

## NSN 5962-01-366-1458

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0