

View Online at <https://aerobasegroup.com/nsn/5962-01-366-3928>

Body Length:

Between 0.342 inches and 0.358 inches

Body Width:

Between 0.342 inches and 0.358 inches

Body Height:

Between 0.060 inches and 0.100 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

3-state output and w/enable and w/disable and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

10 input

Design Function And Quantity:

8 transceiver

Case Outline Source And Designator:

C-2 mil-m-38510

Current Rating Per Characteristic:

6.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Noninverting bus transceiver

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 6.0 volts power source

Capitance Rating Per Characteristic:

10.00 input picofarads and 12.00 output picofarads

Time Rating Per Characteristic:

4.90 nanoseconds propagation delay time, high to low level output and 7.50 nanoseconds propagation delay time, low to high level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0