

View Online at <https://aerobasegroup.com/nsn/5962-01-366-5692>

Maximum Power Dissipation Rating:

600.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Eo lorops e/i fscm 72314

Features Provided:

Programmable

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Design Function And Quantity:

4 reference, voltage, analog

Case Outline Source And Designator:

D-2 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, linear, precision voltage reference, monolithic silicon

Voltage Rating And Type Per Characteristic:

-18.0 volts absolute input and 18.0 volts absolute input

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). And 96906-mil-bul-103 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Specification Data:

67268-5962-89728 government standard

Specification Or Standard:

01 type and e case

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0