

View Online at <https://aerobasegroup.com/nsn/5962-01-367-1266>

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Lgm 030

**Features Provided:**

High speed and presettable and monolithic and electrostatic sensitive

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Complementary transistor logic

**Criticality Code Justification:**

Feat

**Design Function And Quantity:**

1 counter, binary

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, digital, high speed presettable counter, monolithic silicon

**Voltage Rating And Type Per Characteristic:**

4.75 volts total supply and 5.25 volts total supply

**Special Features:**

Esd; hci; selected item is 98747/8746093-01 and radiation tested

**Nuclear Hardness Critical Feature:**

Hardened

**Test Data Document:**

96096-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

14 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0