NSN 5962-01-368-5339

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-368-5339

Body Length:
0.405 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
400.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Adjustable and burn in and w/resistor and externally compensated and electrostatic sensitive
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
2 input
Criticality Code Justification:
Feat
Design Function And Quantity:
1 amplifier, operational, general purpose
Case Outline Source And Designator:
D-4 mil-m-38510
Current Rating Per Characteristic:
3.50 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-18.0 volts power source and 18.0 volts power source
Special Features:
Hardness critical item
Nuclear Hardness Critical Feature:
Hardened
Hardened
Test Data Document:
Test Data Document:
Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

N/a

NSN 5962-01-368-5339

Linear Microcircuit - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A458a0