NSN 5962-01-368-6592

Memory Microcircuit - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/5962-01-368-6592

| 1.490 inches | | | | | | |
|---|--|--|--|--|--|--|
| Overall Height: | | | | | | |
| 0.432 inches | | | | | | |
| Body Length: | | | | | | |
| 1.490 inches | | | | | | |
| Body Width: | | | | | | |
| Between 0.500 inches and 0.610 inches | | | | | | |
| Body Height: | | | | | | |
| Between 0.172 inches and 0.217 inches | | | | | | |
| Maximum Power Dissipation Rating: | | | | | | |
| 1.0 watts | | | | | | |
| Operating Tempurature Range: | | | | | | |
| -55.0/+125.0 degrees celsius | | | | | | |
| Storage Tempurature Range: | | | | | | |
| -65.0/+140.0 degrees celsius | | | | | | |
| Features Provided: | | | | | | |
| Hermetically sealed and burn in and monolithic and programmable | | | | | | |
| Inclosure Material: | | | | | | |
| Ceramic | | | | | | |
| Inclosure Configuration: | | | | | | |
| Dual-in-line | | | | | | |
| Output Logic Form: | | | | | | |
| Complementary-metal oxide-semiconductor logic | | | | | | |
| Input Circuit Pattern: | | | | | | |
| 26 input | | | | | | |
| Criticality Code Justification: | | | | | | |
| Feat | | | | | | |
| Case Outline Source And Designator: | | | | | | |
| D-10 mil-m-38510 | | | | | | |
| Current Rating Per Characteristic: | | | | | | |
| 80.00 milliamperes supply | | | | | | |
| Terminal Surface Treatment: | | | | | | |
| Solder | | | | | | |
| Voltage Rating And Type Per Characteristic: | | | | | | |
| -0.3 volts power source and 6.25 volts power source | | | | | | |
| Time Rating Per Chacteristic: | | | | | | |
| 120.00 nanoseconds access | | | | | | |
| Memory Device Type: | | | | | | |
| Eeprom | | | | | | |
| Memory Capacity: | | | | | | |
| Unknown | | | | | | |

NSN 5962-01-368-6592

Memory Microcircuit - Page 2 of 2



| S | рe | cial | Fe | atu | res: |
|---|----|------|----|-----|------|
|---|----|------|----|-----|------|

Esd; made from pn 5962-8863401xx

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

_0 p.....ou o...ou

Shelf Life:

Unit Of Measure:

N/a

Demilitarization:

Yes - demil/mli

Fiig:

A458a0