

View Online at <https://aerobasegroup.com/nsn/5962-01-368-9931>

Body Length:

1.060 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

148.5 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

5895-01-205-6149 central processing

Features Provided:

3-state output and w/clock and w/enable and low power and schottky and w/disable

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

10 input

Design Function And Quantity:

8 flip-flop, d-type

Case Outline Source And Designator:

D-8 mil-m-38510

Current Rating Per Characteristic:

20.00 microamperes forward current, nonrepetitive, peak total value microamperes

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Characteristic:

17.00 nanoseconds propagation delay time, high to low level output and 14.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A458a0