NSN 5962-01-369-5289

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-369-5289

500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius End Application: Weapon sys processor Features Provided: 3-state output and monolithic Inclosure Configuration: Flat pack Output Logic Form: Complementary-metal oxide-semiconductor logic Criticality Code Justification: Feat Design Function And Quantity: 8 flip-flop, d-type Case Outline Source And Designator: F-9 mil-m-38510
-55.0/+125.0 degrees celsius End Application: Weapon sys processor Features Provided: 3-state output and monolithic Inclosure Configuration: Flat pack Output Logic Form: Complementary-metal oxide-semiconductor logic Criticality Code Justification: Feat Design Function And Quantity: 8 flip-flop, d-type Case Outline Source And Designator:
End Application: Weapon sys processor Features Provided: 3-state output and monolithic Inclosure Configuration: Flat pack Output Logic Form: Complementary-metal oxide-semiconductor logic Criticality Code Justification: Feat Design Function And Quantity: 8 flip-flop, d-type Case Outline Source And Designator:
Weapon sys processor Features Provided: 3-state output and monolithic Inclosure Configuration: Flat pack Output Logic Form: Complementary-metal oxide-semiconductor logic Criticality Code Justification: Feat Design Function And Quantity: 8 flip-flop, d-type Case Outline Source And Designator:
Features Provided: 3-state output and monolithic Inclosure Configuration: Flat pack Output Logic Form: Complementary-metal oxide-semiconductor logic Criticality Code Justification: Feat Design Function And Quantity: 8 flip-flop, d-type Case Outline Source And Designator:
3-state output and monolithic Inclosure Configuration: Flat pack Output Logic Form: Complementary-metal oxide-semiconductor logic Criticality Code Justification: Feat Design Function And Quantity: 8 flip-flop, d-type Case Outline Source And Designator:
Inclosure Configuration: Flat pack Output Logic Form: Complementary-metal oxide-semiconductor logic Criticality Code Justification: Feat Design Function And Quantity: 8 flip-flop, d-type Case Outline Source And Designator:
Flat pack Output Logic Form: Complementary-metal oxide-semiconductor logic Criticality Code Justification: Feat Design Function And Quantity: 8 flip-flop, d-type Case Outline Source And Designator:
Output Logic Form: Complementary-metal oxide-semiconductor logic Criticality Code Justification: Feat Design Function And Quantity: 8 flip-flop, d-type Case Outline Source And Designator:
Complementary-metal oxide-semiconductor logic Criticality Code Justification: Feat Design Function And Quantity: 8 flip-flop, d-type Case Outline Source And Designator:
Criticality Code Justification: Feat Design Function And Quantity: 8 flip-flop, d-type Case Outline Source And Designator:
Peat Design Function And Quantity: 8 flip-flop, d-type Case Outline Source And Designator:
Design Function And Quantity: 8 flip-flop, d-type Case Outline Source And Designator:
8 flip-flop, d-type Case Outline Source And Designator:
Case Outline Source And Designator:
F-9 mil-m-38510
Product Name:
Mckt, dgtl-advanced cmos inter face logic
Voltage Rating And Type Per Characteristic:
4.5 volts total supply and 5.5 volts total supply
Special Features:
Esd; hci. This item should be a selected item dwg not source control. This item is a 67268 5962-8762802sa
Terminal Type And Quantity:
20 beam lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0