

View Online at <https://aerobasegroup.com/nsn/5962-01-369-6179>

Body Length:

Between 0.370 inches and 0.390 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.065 inches and 0.085 inches

Maximum Power Dissipation Rating:

148.5 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Weapon system processor

Features Provided:

Burn in, mil-std-883, class b and cascable and low power and schottky and monolithic and presettable

Inclosure Material:

Ceramic

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

3 input

Criticality Code Justification:

Feat

Design Function And Quantity:

1 counter, decade, up/down

Case Outline Source And Designator:

F-2 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital, ttl logic

Voltage Rating And Type Per Characteristic:

4.5 volts total supply and 5.5 volts total supply

Special Features:

Esd; hci; item 01295/snj54ls196w (which is 14933/7701001da or 81349/m38510/32001bda) was tested and met the hci criteria

Nuclear Hardness Critical Feature:

Hardened

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0