

View Online at <https://aerobasegroup.com/nsn/5962-01-369-6179>

**Body Length:**

Between 0.370 inches and 0.390 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.065 inches and 0.085 inches

**Maximum Power Dissipation Rating:**

148.5 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Weapon system processor

**Features Provided:**

Burn in, mil-std-883, class b and cascable and low power and schottky and monolithic and presettable

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

3 input

**Criticality Code Justification:**

Feat

**Design Function And Quantity:**

1 counter, decade, up/down

**Case Outline Source And Designator:**

F-2 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, digital, ttl logic

**Voltage Rating And Type Per Characteristic:**

4.5 volts total supply and 5.5 volts total supply

**Special Features:**

Esd; hci; item 01295/snj54ls196w (which is 14933/7701001da or 81349/m38510/32001bda) was tested and met the hci criteria

**Nuclear Hardness Critical Feature:**

Hardened

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

14 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0