## NSN 5962-01-369-6834

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-369-6834

Body Length:
1.060 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
1.1 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Bipolar and programmed and high impedance and w/enable and w/disable and electrostatic sensitive and w/clock
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
9 input
Case Outline Source And Designator:
D-8 mil-m-38510
Current Rating Per Characteristic:
90.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
Registered and-or gate array
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 12.0 volts power source
Memory Device Type:
Pal
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.)
Terminal Type And Quantity:
20 printed circuit
Shelf Life:
N/a
Unit Of Measure:

## NSN 5962-01-369-6834

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0