

View Online at <https://aerobasegroup.com/nsn/5962-01-369-9227>

Maximum Power Dissipation Rating:

357.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

C-17a aircraft e/i fscm 88277

Features Provided:

Low power and schottky

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Design Function And Quantity:

8 counter, digital

Case Outline Source And Designator:

C-2 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital, low power schottky ttl, binary counter. Monolithic silicon

Voltage Rating And Type Per Characteristic:

-0.5 volts total supply and 7.0 volts total supply and 4.5 volts positive power supply span and 5.5 volts positive power supply span

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 printed circuit

Specification Data:

67268-5962-87517 government standard

Specification Or Standard:

01 type and 2 case and a finish

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0