NSN 5962-01-370-0384

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-370-0384

Body Length: 1.060 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 2.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Bipolar and programmed and high impedance and w/enable and w/disable and electrostatic sensitive and w/clock **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 9 input **Case Outline Source And Designator:** D-8 mil-m-38510 **Current Rating Per Characteristic:** 180.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Product Name:** Registered and-or gate array Voltage Rating And Type Per Characteristic: -0.5 volts power source and 12.0 volts power source

Memory Device Type:

Pal

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

NSN 5962-01-370-0384

Memory Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

