

View Online at <https://aerobasegroup.com/nsn/5962-01-370-1474>

**Maximum Power Dissipation Rating:**

1.04 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Bipolar

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Bipolar metal-oxide semiconductor

**Case Outline Source And Designator:**

D-3 mil-m-38510

**Current Rating Per Characteristic:**

100.00 milliamperes reverse current, dc

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, digital, schottky, bipolar 65536 bit prom

**Voltage Rating And Type Per Characteristic:**

-0.3 volts total supply and 7.0 volts total supply

**Time Rating Per Characteristic:**

55.00 nanoseconds access

**Memory Device Type:**

Prom

**Hybrid Technology Type:**

Monolithic

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0