NSN 5962-01-370-2385

Memory Microcircuit - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5962-01-370-2385 |
|--|
| Body Length: |
| 0.640 inches |
| Body Width: |
| Between 0.360 inches and 0.420 inches |
| Body Height: |
| Between 0.045 inches and 0.090 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Programmed and electrostatic sensitive |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Flat pack |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Current Rating Per Characteristic: |
| 185.00 milliamperes reverse current, dc absolute |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| Microcircuit 32768bit prom |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts total supply and 7.0 volts total supply |
| Memory Device Type: |
| Prom |
| Test Data Document: |
| 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 |
| standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 24 flat leads |
| Specification Data: |
| 03640-104a154 manufacturers specification |
| Specification Or Standard: |
| -14 number |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

NSN 5962-01-370-2385

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0