NSN 5962-01-370-2386



Memory Microcircuit - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5962-01-370-2386
Body Length:
0.640 inches
Body Width:
Between 0.360 inches and 0.420 inches
Body Height:
Between 0.045 inches and 0.090 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Programmed
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Current Rating Per Characteristic:
185.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit 32768bit prom
Voltage Rating And Type Per Characteristic:
-0.5 volts total supply and 7.0 volts total supply
Memory Device Type:
Prom
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883
standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
24 flat leads
Specification Data:
03640-104a154 manufacturers specification
Specification Or Standard:
-15 number
Shelf Life:
N/a

Demilitarization: Voc. domil/mli

Unit Of Measure:

NSN 5962-01-370-2386

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0