## NSN 5962-01-370-3701

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-370-3701

Body Length:
--------------

Between 0.750 inches and 0.770 inches

**Body Width:** 

Between 0.260 inches and 0.300 inches

**Body Height:** 

Between 0.160 inches and 0.200 inches

**Maximum Power Dissipation Rating:** 

900.0 milliwatts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

**End Application:** 

F15 serd 8321 e/i fscm 76301

**Features Provided:** 

Monolithic and high speed and low impedance and low voltage

**Inclosure Material:** 

Ceramic

**Inclosure Configuration:** 

Dual-in-line

**Input Circuit Pattern:** 

Quad 1 input

**Design Function And Quantity:** 

4 switch, analog, single pole single throw normally open

**Current Rating Per Characteristic:** 

30.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:** 

Solder

**Product Name:** 

Microcircuit, switch, analog, quad spst cmos

**Voltage Rating And Type Per Characteristic:** 

-44.0 volts total supply and 44.0 volts total supply

**Terminal Type And Quantity:** 

16 printed circuit

**Specification Data:** 

81873-84001898 manufacturers specification

**Specification Or Standard:** 

002 number

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5962-01-370-3701

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0