

View Online at <https://aerobasegroup.com/nsn/5962-01-370-4949>

Body Length:

1.290 inches

Body Width:

Between 0.500 inches and 0.610 inches

Body Height:

0.210 inches

Maximum Power Dissipation Rating:

1.02 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

W/buffered output and w/enable and w/active pull-up and 3-state output and high impedance and programmed and schottky and bipolar

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

14 input

Criticality Code Justification:

Feat

Case Outline Source And Designator:

D-3 mil-m-38510

Current Rating Per Characteristic:

185.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Czd-3

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Characteristic:

100.00 nanoseconds access

Memory Device Type:

Prom

Special Features:

Nuclear hardness critical item

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0