NSN 5962-01-370-6614



Digital Microcircuit - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5962-01-370-6614	
Body Length:	
2.096 inches	
Body Width:	
Between 0.510 inches and 0.620 inches	
Body Height:	
0.210 inches	
Maximum Power Dissipation Rating:	
0.4 watts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Electrostatic sensitive and bidirectional and w/clock and w/disable and monolithic	
Inclosure Material:	
Ceramic	
Inclosure Configuration:	
Dual-in-line	
Output Logic Form:	
Complementary-metal oxide-semiconductor logic	
Input Circuit Pattern:	
18 input	
Criticality Code Justification:	
Feat	
Design Function And Quantity:	
1 processor, input	
Case Outline Source And Designator:	
D-5 mil-m-38510	
Current Rating Per Characteristic:	
65.00 milliamperes reverse current, dc absolute	
Terminal Surface Treatment:	
Solder	
Product Name:	
Digital signal processor	
Voltage Rating And Type Per Characteristic:	

-0.3 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

25.00 input picofarads and 25.00 output picofarads

Special Features:

Nuclear hardness critical item

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

NSN 5962-01-370-6614

Digital Microcircuit - Page 2 of 2



Terminal Type Aı	nd Quantity:
------------------	--------------

40 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0