

View Online at <https://aerobasegroup.com/nsn/5962-01-370-6639>

Body Length:

1.490 inches

Body Width:

Between 0.500 inches and 0.610 inches

Body Height:

0.217 inches

Maximum Power Dissipation Rating:

0.75 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Electrostatic sensitive and bidirectional and w/disable and w/enable and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

21 input

Criticality Code Justification:

Feat

Case Outline Source And Designator:

D-10 mil-m-38510

Current Rating Per Characteristic:

120.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Nonvolatile static ram

Voltage Rating And Type Per Characteristic:

-1.0 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

6.00 input pascal industrial light tank stock and 10.00 output pascal industrial light tank stock

Time Rating Per Chacteristic:

300.00 nanoseconds access

Memory Device Type:

Ram

Special Features:

Hardness critical item

Nuclear Hardness Critical Feature:

Hardened

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0