

View Online at <https://aerobasegroup.com/nsn/5962-01-370-6639>

**Body Length:**

1.490 inches

**Body Width:**

Between 0.500 inches and 0.610 inches

**Body Height:**

0.217 inches

**Maximum Power Dissipation Rating:**

0.75 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Electrostatic sensitive and bidirectional and w/disable and w/enable and monolithic

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

21 input

**Criticality Code Justification:**

Feat

**Case Outline Source And Designator:**

D-10 mil-m-38510

**Current Rating Per Characteristic:**

120.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Product Name:**

Nonvolatile static ram

**Voltage Rating And Type Per Characteristic:**

-1.0 volts power source and 7.0 volts power source

**Capitance Rating Per Characteristic:**

6.00 input pascal industrial light tank stock and 10.00 output pascal industrial light tank stock

**Time Rating Per Characteristic:**

300.00 nanoseconds access

**Memory Device Type:**

Ram

**Special Features:**

Hardness critical item

**Nuclear Hardness Critical Feature:**

Hardened

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

28 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0