

View Online at <https://aerobasegroup.com/nsn/5962-01-370-7294>

Body Length:

Between 0.640 inches and 0.660 inches

Body Width:

Between 0.065 inches and 0.660 inches

Maximum Power Dissipation Rating:

1.0 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

W/strobe and w/enable and w/disable and monolithic and electrostatic sensitive

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Design Function And Quantity:

1 latch and 1 multiplexer

Current Rating Per Characteristic:

10.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Parallel i/o

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Capitance Rating Per Characteristic:

7.00 input picofarads and 10.00 output picofarads

Time Rating Per Characteristic:

400.00 nanoseconds access

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

40 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0