NSN 5962-01-370-7304

Memory Microcircuit - Page 1 of 2

Demilitarization: Yes - demil/mli



View Online at https://aerobasegroup.com/nsn/5962-01-370-7304 **Body Length:** Between 0.930 inches and 0.970 inches **Body Width:** Between 0.245 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.175 inches **Maximum Power Dissipation Rating:** 490.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** W/enable and bidirectional and programmed and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 16 input **Current Rating Per Characteristic:** 70.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Product Name:** And or gate array Voltage Rating And Type Per Characteristic: 7.0 volts power source **Memory Device Type:** Pal **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 printed circuit Shelf Life: N/a **Unit Of Measure:**

NSN 5962-01-370-7304

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0