

View Online at <https://aerobasegroup.com/nsn/5962-01-370-7310>

**Body Length:**

Between 1.270 inches and 1.290 inches

**Body Width:**

Between 0.290 inches and 0.320 inches

**Body Height:**

Between 0.180 inches and 0.225 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Pacer special

**Features Provided:**

3-state output and schottky and programmable and electrostatic sensitive and tested to mil-std-883 and burn in, mil-std-883, class b and hermetically sealed

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

14 input

**Case Outline Source And Designator:**

D-9 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Product Name:**

Integrated circuit-modified transec microcode

**Voltage Rating And Type Per Characteristic:**

-0.5 volts total supply and 5.5 volts total supply

**Memory Device Type:**

Prom

**Memory Capacity:**

16384 x 2048

**Special Features:**

Electrostatic discharge sens/hardness critical item; altered item programmed (using 34335/am27s45/bla) using file tpmu18.Hex with checksum 43af. Crit code chg (h) per es lonnell may 01/06

**Nuclear Hardness Critical Feature:**

Hardened

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Specification Data:**

95105-210-2155-010 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0